# **SILVERLINK 600**



BM7BW - Lincat Silverlink 600 Electric Counter-top Bain Marie - Wet Heat -Gastronorms - Base + Dish Pack - W 750 mm -2.0 kW The Silverlink 600 Electric Wet Heat Bain Marie safely holds sauces, soups, gravy and precooked foods for up to two hours at the ideal serving temperature

- Wet heat bain marie
- Ideal for holding foods for up to 2 hours at serving temperature
- 3 x 1/6 plus 2 x 1/4 and 2x 1/2 150mm deep gastronorms with lids are included
- This wet unit can also be used as a dry bain marie
- Plug and play for an easy installation
- Perfect for safely holding sauces, gravy & precooked foods
- Adjustable temperature control

2.000

8.7

230

### **Specifications**

Summary     Power and Performance       Brand     Lincat     Total Power kW     2.00       Range     Silverlink 800     IP Rating     1P33       Power Type     Electric     Temperature Control     Mechanical       Unit Type     Counter-top     Mechanical       Available in UK Only     No     No       UK Warranty     2 Years Parts and Labour Warranty     Export Warranty     Contact your local dealer       GTIN     5056105100645     Capacity          2x GNI/2: 2x GNI/4; 3x GNI/6         Pot Type         Gastronorm       Pot Type     Gastronorm     2x GNI/2: 2x GNI/4; 3x GNI/6         Pot Type of Heat     Wet       Weights and Dimensions       Supply Connections       Unit Height (External) mm     290     Requires Installation     No       Unit Unit Width (External) mm     750     Requires Electrical Supply     Yes       Unit Depth (External) mm     600     UK 3 Pin Plug     Yes       No	Specifications			
Range Silverlink 600 IP Rating IP33 Power Type Electric Temperature Control Mechanical Unit Type Counter-top Available in UK Only No UK Warranty 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer GTIN 5056105100645  Key Specifications Front-mounted Gastronorm Type Gastronorm Type Gastronorm Type of Heat Wet  Weights and Dimensions Supply Connections  Requires Installation No Init Width (External) mm Unit Width (External) mm Onit Width (External) mm Onit Depth (External) mm Onit Width (External) mm Onit Depth (Extern	Summary		Power and Performance	
Power Type       Electric       Temperature Control       Mechanical         Unit Type       Counter-top       Available in UK Only       No         UK Warranty       2 Years Parts and Labour Warranty       Export Warranty       Contact your local dealer 5056105100645         CTIN       Capacity       Export Warranty         Corpain Location Pot Type Type of Heat       Front-mounted Gastronorm       Gastronorm         Type of Heat       Wet         Weights and Dimensions         Supply Connections         Unit Height (External) mm Unit Width (External) mm       290       Requires Installation Requires Electrical Supply Yes       No Requires Electrical Supply Yes         Unit Depth (External) mm Unit Depth (External) mm       500       UK 3 Pin Plug       Yes	Brand	Lincat	Total Power kW	2.00
Unit Type   Counter-top   No   No   UK Warranty   2 Years Parts and Labour Warranty   Export Warranty   Contact your local dealer   S056105100645   Capacity    Key Specifications   Front-mounted   Gastronorm Capacity   C	Range	Silverlink 600	IP Rating	IP33
Available in UK Only UK Warranty Export Warranty GTIN  Contact your local dealer 5056105100645   Capacity	Power Type	Electric	Temperature Control	Mechanical
UK Warranty Export Warranty GTIN  Contact your local dealer 5056105100645   Key Specifications  Capacity  Drain Location Pot Type Gastronorm Type of Heat  Wet  Wet  Weights and Dimensions  Unit Height (External) mm Unit Width (External) mm 750 Requires Electrical Supply UK 3 Pin Plug  Ves	Unit Type	Counter-top		
Export Warranty GTIN  Contact your local dealer 5056105100645  Key Specifications  Capacity  Pot Type Type of Heat  Wet  Weights and Dimensions  Pot Type Unit Height (External) mm Unit Width (External) mm Unit Weight (External) mm 000 000 000 000 000 000 000 000 000	Available in UK Only	No		
GTIN       5056105100645         Key Specifications       Capacity         Drain Location Pot Type Pot Type Gastronorm       Front-mounted Gastronorm       Gastronorm Capacity       2 x GN1/2; 2 x GN1/4; 3 x GN1/6         Type of Heat       Weights and Dimensions         Supply Connections         Unit Height (External) mm       290       Requires Installation Requires Electrical Supply       No         Unit Width (External) mm       750       Requires Electrical Supply       Yes         Unit Depth (External) mm       600       UK 3 Pin Plug       Yes	UK Warranty	2 Years Parts and Labour Warranty		
Key Specifications  Capacity  Drain Location Pot Type Gastronorm Type of Heat  Weights and Dimensions  Unit Height (External) mm 290 Requires Installation Unit Width (External) mm 750 Requires Electrical Supply Unit Depth (External) mm 600  UK 3 Pin Plug  Yes	Export Warranty	Contact your local dealer		
Drain Location Front-mounted Gastronorm Capacity 2 x GN1/2; 2 x GN1/4; 3 x GN1/6 Pot Type Gastronorm Type of Heat Wet  Weights and Dimensions  Unit Height (External) mm 290 Unit Width (External) mm 750 Requires Electrical Supply Yes Unit Depth (External) mm 600  UK 3 Pin Plug Yes	GTIN	5056105100645		
Pot Type       Gastronorm         Type of Heat       Supply Connections         Weights and Dimensions       Supply Connections         Unit Height (External) mm       290       Requires Installation       No         Unit Width (External) mm       750       Requires Electrical Supply       Yes         Unit Depth (External) mm       600       UK 3 Pin Plug       Yes	Key Specifications		Capacity	
Type of Heat Wet  Weights and Dimensions  Supply Connections  Unit Height (External) mm 290 Requires Installation No Unit Width (External) mm 750 Requires Electrical Supply Yes Unit Depth (External) mm 600 UK 3 Pin Plug Yes	Drain Location	Front-mounted	Gastronorm Capacity	2 x GN1/2; 2 x GN1/4; 3 x GN1/6
Weights and Dimensions  Unit Height (External) mm 290 Requires Installation No Unit Width (External) mm 750 Requires Electrical Supply Yes Unit Depth (External) mm 600 UK 3 Pin Plug Yes	Pot Type	Gastronorm		
Unit Height (External) mm 290 Requires Installation No Unit Width (External) mm 750 Requires Electrical Supply Yes Unit Depth (External) mm 600 UK 3 Pin Plug Yes	Type of Heat	Wet		
Unit Width (External) mm750Requires Electrical SupplyYesUnit Depth (External) mm600UK 3 Pin PlugYes	Weights and Dimensions		Supply Connections	
Unit Depth (External) mm 600 UK 3 Pin Plug Yes	Unit Height (External) mm	290	Requires Installation	No
	Unit Width (External) mm	750	Requires Electrical Supply	Yes
Net Weight Kg 22.9 Requires Hardwiring No	Unit Depth (External) mm	600	UK 3 Pin Plug	Yes
	Net Weight Kg	22.9	Requires Hardwiring	No

**Electrical Supply Rating Watts** 

Single Phase Amps

Single Phase Voltage

### Shipping

Packed Weight Kg	25.19
Packed Height cm	49.5
Packed Width cm	85.5
Packed Depth cm	70

### **Available Accessories**

CC7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 750 mm

CN7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm

Product Code: BM7BW Page Number: 1 Print Date: 26/08/2022




## **Available Accessories**


**HC7** Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 750 mm - 0.5 kW


HCL7 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 750 mm - 0.75 kW

**SLS7** Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm

## **Technical Picture**













**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Omica migaom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm

