lincat





DF4/N - Lincat Silverlink 600 Natural Gas Countertop Single Tank Fryer - 2 Baskets - W 450 mm - 11.3 kW

- Single tank fryer with twin basket operation giving you the flexibility to cook different foods or loads simultaneously, delivering 25kg of chips per hour
- Front mounted controls for safety
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris gives cleaner cooking results and saves money by prolonging the life of the oil

The Silverlink 600 Gas Single Tank Counter Top Fryer delivers 25kg of chips per hour, while it also features a twin basket operation which gives you the flexibility of cooking different foods or loads simultaneously.

- Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Front drain off tap for easy removal of cooking oil

Specifications

opecifications			
Summary		Power and Performance	
Brand	Lincat	BTU per Hour	38,555
Range	Silverlink 600	Total Power kW	11.3
Power Type	Gas	Temperature Range °C	110-190
Gas Type	Natural Gas	Temperature Control	Mechanical
Unit Type	Counter-top		
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105104605		
Key Specifications		Capacity	
Number of Baskets	2	Product Output per Hour	16kg chips - 12mm [frozen], 25kg chips -
Number of Tanks	1	i loudet output per flour	12mm[chi
Gravity Filtration	No	Capacity Litres	8.0
Pumped Filtration	No		
Drain Location	Front-mounted		
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	415	Requires Installation	Yes
Unit Width (External) mm	450	Requires Electrical Supply	No
Unit Depth (External) mm	654	Gas Connection BSP	1/2"
Net Weight Kg	30.9	Gas Consumption at full rate Natural m ³ per Hour	1.08
		Gas Pressure Natural mbar	16.2
		Total heat input at full rate Natural kW	11.3

Total heat input at full rate Natural

BTU per hour

38,600

lincat


SILVERLINK 600


Shipping


Packed Weight Kg	43.2
Packed Height cm	63.5
Packed Width cm	70
Packed Depth cm	55

Available Accessorie	es
CH01	Caterflex Hose 1/2" - 1 Metre - for use with units up to 66,000 BTU
CH02	Caterflex Hose 1/2" - 1.5 Metre - for use with units up to 56,000 BTU
CN4	Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm
DC01	DONUT CONV KIT DF4/GAS
SLS4	Lincat Silverlink 600 Free-standing Floor Stand - for units W 450 mm

Technical Picture









SILVERLINK 600

Lincat frifri

Lincat Limited

Whisby Road, Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250 Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm