



P6B3 - Lincat Panther 670 Series Free-standing Hot Cupboard - Bain Marie Top - 3GN - W 1205 mm - 2.8 kW

A great solution for holding and transporting food at the perfect temperature, the Panther 670 Series Hot Cupboard / Bain Marie is designed to fit through narrow doorways, so is ideal for pubs and smaller restaurants as well as nursing and care homes where plated meals are to be transported from the kitchen to the residents.

- Ideal to to fit through narrow corridors and doorwavs
- Bain marie top, ideal for small restaurants, cafes and pubs, as well as nursing and care homes. where the easy transportation of plated meals to diners and residents is a necessity
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 3 x 1/1 GN containers up to 150mm deep.
- Thermostatically controlled bain marie top can be operated with wet or dry heat. Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads
- Drain tap located inside the hot cupboard allows fast and easy draining

302

Specifications

Number of Shelves included

Number of Shelf Positions

Pot Type

Type of Heat

Heated Base

Heated Gantry

Static or Mobile

2

4

Gastronorm

Wet/Dry

Yes

Nο

Mohile

Summary Power and Performance Brand Total Power kW 2.85 Lincat Temperature Range °C Range Panther 20-99 Series IP Rating 670 Series **Power Type Temperature Control** Electric Top: Mechanical; Bottom: Electronic **Unit Type** Free-standing Available in UK Only Nο **UK Warranty** 2 Years Parts and Labour Warranty **Export Warranty** Contact your local dealer **GTIN** 5056105103400 **Key Specifications** Capacity **Drain Location Gastronorm Capacity** 3 x GN1/1 Right side interior mounted

Plate Capacity





Weights and Dimensions		Supply Connections	
Unit Height (External) mm	912	Requires Installation	No
Unit Width (External) mm	1205	Requires Electrical Supply	Yes
Unit Depth (External) mm	672	UK 3 Pin Plug	Yes
Height (Internal) mm	432	Requires Hardwiring	No
Width (Internal) mm	1,020	Electrical Supply Rating Watts	2,850
Depth (Internal) mm	512	Single Phase Amps	12.4
Shelf Dimensions Width mm	966	Single Phase Voltage	230
Shelf Dimensions Depth mm	512		
Net Weight Kg	95.6		
Shipping			
Packed Weight Kg	105.16		
Packed Height cm	103		
Packed Width cm	120		
Packed Depth cm	80		

	1	<i>ı</i> ai	la	hl	Δ.	O	pti	O	ns
-	-	Zei	ш	ы.		v	Pu	U	LC

Overshe	elf or	Gantry	
---------	--------	--------	--

PG3A PG3A - Ambient Gantry
PG3H PG3H - Heated Gantry
PS3A1 PS3A1 - 1 Ambient Overshelf
PS3A2 PS3A2 - 2 Ambient Overshelves
PS3A3 PS3A3 - 3 Ambient Overshelves
PS3H1 PS3H1 - 1 Heated Overshelf

PS3H2 PS3H2 - 2 Heated Overshelves
PS3H3 - 3 Heated Overshelves

Door Locks

PDL3 - Lockable Door

Corner Guards

PCG - Corner Guards [Set of Four]

Trayslides

PTS3 - Tray Slide

Legs/Castors


PLK PLK - Legs[non chargeable]


Avai	labi	le A	cces	sori	ies


CP16	CP16 - CARVERY PAD[1/1 GASTRONORM SIZE]
PGK4	PGK4 - GASTRONORM PACK
PGK5	PGK5 - GASTRONORM PACK
PGK6	PGK6 - GASTRONORM PACK
PGK7	PGK7 - GASTRONORM PACK
PHTC	PHTC - CERAMIC INSERT [1/1 GASTRONORM SIZE]
PHTG	PHTG - GLASS INSERT[1/1 GASTRONORM SIZE]
PLK/S	PLK/S - LEG KIT [FOR CONVERSION IN THE FIELD]
PPB6	PPB6 - ADDITIONAL PUSHBAR



Technical Picture









Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm