



Sirman Spa  
 Viale dell'Industria 9/11  
 35010 PIEVE DI CURTAROLO (PD), Italy  
 Tel./Fax. +39 049 9698666 / +39 049 9698688  
 email: info@sirman.com



Sirman Slicers , model Palladio 300 Aut. :

- Rounded design, no sharp edges and visible screws.
- Chrome plated and ground slide rod.
- Lapped cast iron slide rod bushing.
- Vulcanized rubber stops on carriage.
- Removable support cover for thickness gauge plate.
- Stainless steel slice deflector with bayonet fitting.
- Stainless steel screws and fittings.
- Enclosed and sealed belt pulley.
- 49,5 mm distance between blade and motor.
- Bottom cover.
- Power source 220V.
- Built in sharpening tool with bottom protection.
- Standard blade removal tool.
- Ergonomic controls – push buttons with IP67 protection rating.
- 3 speed selection
- 3 different adjustments for carriage travel.
- Uniko hopper.
- Slice counter.
- Slice number setting with automatic stop feature.
- Enclosed and sealed drive motor.
- Positive drive belt.
- Carriage release system for manual slicing.
- Output slicers per minute: 37 - 70

**Optional accessories:**

- Carriage "Nettuno" available with a special end weight and an adjustable vertical product fence to provide stability and advance products evenly
- Food fence



More space between blade and body machine






Optional Nettuno hopper



Controls

Data sheet



Technical data

Model	PALLADIO 300 AUT.
ø blade	mm 300 - inch. 12
Motor	watt 275+200 - Hp 0,37+0,27
Cut of thickness	mm 23
Run of carriage	mm 310
Hopper	mm 365x270
A	mm 465
B	mm 340
C	mm 615
D	mm 660
E	mm 465

F	mm 730
G	mm 650
L	mm 600
X	mm 240/270
Y	mm 190
H	mm 240
W	mm 220
Net weight	kg 38
Shipping	mm 870x840x750
Gross weight	kg 53
HS-CODE	84385000